TECHNICAL DATA SHEET

KEIM DESIGN-FIXATIV

1. PRODUCT DESCRIPTION

Sol-silicate-based thinner and primer for KEIM Design-Lasur. KEIM Design-Fixativ has been awarded Cradle to Cradle Certified® Full Scope Silver, Material Health Gold and Circularity Silver in accordance with Version 5.0.

2. FIELD OF APPLICATION

KEIM Design-Fixativ is used for the pre-treatment of highly absorbent substrates and as a thinner for highly transparent glazes with KEIM Design-Lasur.
By applying two to three coats of KEIM Design-Lasur and KEIM Design-Fixativ, highly transparent glazes can be achieved, especially in the full-tone range. Attractive effects can also be achieved by using the same colour tone in different dilution levels.

3. PRODUCT PROPERTIES

- Cradle to Cradle Certified® Full Scope Silver (Version 5.0)
- Cradle to Cradle Certified® Material Health Gold (Version 5.0)
- Cradle to Cradle Certified® Circularity Silver (Version 5.0)
- lightfast
- weather-resitant

MATERIAL CHARACTERISTICS:

– Density	approx. 1.0 g/cm³ - 1.1 g/cm³
– pH value	approx. 11

COLOUR SHADES:
milky

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:
The substrate must be solid, dry, clean, sound and free from residues that may impair adhesion.

APPLICATION CONDITIONS:
The air and substrate temperature must be between ≥ 5 °C and ≤ 30 °C during application and drying. Do not apply in direct sunlight or on substrates heated by the sun. Protect surfaces from direct sunlight, wind and rain during and after application.

CONSUMPTION:
approx. 0,05 L/m² for ready-to-use mixture of KEIM Design-Lasur and KEIM Design-Fixativ
The information on material consumption is a guide for smooth substrates. Exact consumption figures must be determined by carrying out test areas.

PROCESSING:
KEIM Design-Fixativ is particularly recommended as a thinner for highly transparent glazes and for glazes in the solid tone range. The prepared glaze must always be stirred well before and during work. Water or other materials must not be added. The glaze is applied with a suitable glaze brush (e.g. oval KEIM glaze brush) using the crosswise technique. When applying the glaze, it is important to work quickly and avoid build-up.

Note: The system components of the KEIM Design-Lasur system, Design-Lasur, Design-Base and KEIM Design-Fixativ can be mixed with each other in any ratio. KEIM Design-Base results in beautiful transparency with ideal processing consistency and layer thickness. KEIM Design-Fixativ allows highly transparent, colour-brilliant glazes with low layer thickness.

CLEANING OF TOOLS:
Clean immediately with water.

5. PACKAGING

Container content	Unit of measure	Quantity on pallet	Type of container
20	L	24	jerry can
5	L	96	jerry can

6. STORAGE

Maximum storage time	Storage conditions
12 months	cool frost-free keep container tightly sealed. protected from heat and direct sun.

7. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

Waste code: 06 02 99

8. SAFETY INSTRUCTIONS

Refer to the safety data sheet. EU limit value for this product (Cat. A/h): 30 g/l.
This product contains: 0 - 1 g/l VOC.

GIS code: BSW 10

9. GENERAL INFORMATION

Cover surfaces not to be treated, particularly glass, ceramics and natural stone. Splashes on surrounding surfaces or traffic areas must be immediately diluted with plenty of water and removed.
Mixing with products from other systems or other external additives is not permitted.

10. CERTIFICATES & QUALITY SEALS

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.

KEIMFARBEN GMBH
Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0
www.keim.com / info@keimfarben.de