TECHNICAL DATA SHEET

KEIM STONECLEANER-N

1. PRODUCT DESCRIPTION

Neutral cleaning concentrate on an aqueous basis

2. FIELD OF APPLICATION

KEIM Stonecleaner-N is a cleaning concentrate adapted to the requirements of steam-blasting equipment. Due to its wide range of applications, KEIM Stonecleaner-N is suitable for universal use, especially for mild and gentle cleaning of stubborn dust, grease, oil and soot stains on natural stone, concrete and clinker facades.

3. PRODUCT PROPERTIES

- aqueous
- universally applicable

MATERIAL CHARACTERISTICS:

– Density	approx. 1.0 g/cm³ - 1.1 g/cm³
– pH value	approx. 7,1

COLOUR SHADES:
yellow-brown

4. APPLICATION INSTRUCTIONS

MATERIAL PREPARATION:

CONSUMPTION:
Determine consumption on the basis of sample surfaces.
The information on material consumption is a guide for smooth substrates. Exact consumption figures must be determined by carrying out test areas.

PROCESSING:
Precoat atmospherically soiled surfaces with KEIM Stonecleaner-N, diluted 1:10 with water. After an exposure time of at least 1 hour, remove soiling from the bottom to the top using water pressure jetting (hot or cold).
Or KEIM Stonecleaner-N, diluted 1:10 with water, add to the dosing container of the steam jet unit. Then clean soiled surfaces from bottom to top using the water pressure jet method. Afterwards, the cleaned surfaces must be rinsed with clear water.
Note: Not suitable for removing crusty soiling.

TOP COAT:

PAINT STRUCTURE:

POST-TREATMENT:

CLEANING OF TOOLS:
Clean immediately with water.

5. PACKAGING

Container content	Unit of measure	Type of container
10	kg	jerry can

6. STORAGE

Maximum storage time	Storage conditions
12 months	frost-free keep container tightly sealed.

7. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

Waste code: 16 10 01 *

8. SAFETY INSTRUCTIONS

Refer to the Safety Data Sheet and Technical Data Sheet. For professional use only.

GIS code: GF 0

9. GENERAL INFORMATION

Cover surfaces not to be treated, particularly glass, ceramics and natural stone. Splashes on surrounding surfaces or traffic areas must be immediately diluted with plenty of water and removed.
Mixing with products from other systems or other external additives is not permitted.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.

KEIMFARBEN GMBH
Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0
www.keim.com / info@keimfarben.de